

View Online at <https://aerobasegroup.com/nsn/5320-01-399-8367>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Green

**Fastener Length:**

Between 0.440 inches and 0.460 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.3765 inches and 0.3813 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.120 inches and 0.130 inches

**Min. Tensile Strength (psi):**

4350 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

7060 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Grit blast top of head, with color green on thread end.

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

76823-03a063 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0