NSN 5320-01-400-1895

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-400-1895 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.753 inches and 1.773 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.433 inches and 1.443 inches Min. Tensile Strength (psi): 2000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 73197-hl11 manufacturers standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-400-1895

Pin-rivet - Page 2 of 2



Fiig:

A528u0