NSN 5320-01-400-1901

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-400-1901



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.565 inches and 1.585 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.245 inches and 1.255 inches

Min. Tensile Strength (psi):

2000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

5380 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

73197-hl11 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-400-1901

Pin-rivet - Page 2 of 2

Fiig: A528u0

