
# NSN 5320-01-400-1902

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.635 inches and 1.655 inches

# Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

# Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 0.415 inches and 0.440 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

Between 1.245 inches and 1.255 inches

# Min. Tensile Strength (psi):

5820 pounds per square inch

# Thread Size:

0.250 inches

# Shear Strength:

9300 double pounds per square inch

# Material:

Titanium alloy uns r56400

# **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

# **Thread Series Designator:**

Unjf

#### **Specification Data:**

73197-hl12 manufacturers standard

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-400-1902

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

