# NSN 5320-01-408-0551

Pin-rivet - Page 1 of 2



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.822 inches and 0.842 inches

## Head Style:

Err-090

### Head Height:

Between 0.059 inches and 0.069 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2641 inches and 0.2651 inches

### Shank Style:

## Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 0.432 inches and 0.442 inches

# Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### Surface Treatment:

Aluminum

## Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No



# NSN 5320-01-408-0551

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

