

View Online at <https://aerobasegroup.com/nsn/5320-01-408-3366>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.038 inches and 1.058 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.045 inches and 0.055 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.2329 inches and 0.2339 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.320 inches and 0.340 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.683 inches and 0.693 inches

**Thread Size:**

0.190 inches

**Special Features:**

0.0468 oversize shank, restricted usage, repair only

**Material:**

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp e4340

**Material Specification:**

Mil-s-6758 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-5000 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2. Federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

81205-bacb30ma manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6758 spec.