

View Online at <https://aerobasegroup.com/nsn/5320-01-408-3366>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.038 inches and 1.058 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2329 inches and 0.2339 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.320 inches and 0.340 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.683 inches and 0.693 inches

Thread Size:

0.190 inches

Special Features:

0.0468 oversize shank, restricted usage, repair only

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-6758 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-5000 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2. Federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

81205-bacb30ma manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.