
## NSN 5320-01-408-8521

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.100 inches and 1.120 inches

## Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2329 inches and 0.2339 inches

#### Shank Style:

## Head Major Diameter:

Between 0.380 inches and 0.400 inches

#### End Application:

W/s: aircraft, stratolifter c-135

## Grip Length:

Between 0.745 inches and 0.755 inches

#### **Thread Size:**

0.190 inches

## Special Features:

0.0468 oversized shank, for repair work only.

## Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740

## Material Specification:

Mil-s-6758 military specification single material response or mil-s-5628 military specification single material response or mil-s-8740 military

specification single material response

## Surface Treatment:

Cadmium

## **Surface Treatment Specification:**

Qq-p-416, type ii, class 2. Federal specification single treatment response

## Thread Series Designator:

Unjf

## **Specification Data:**

81205-bacb30me manufacturers standard

## Shelf Life:

N/a

#### Unit Of Measure:



# NSN 5320-01-408-8521

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.

