

View Online at <https://aerobasegroup.com/nsn/5320-01-408-8549>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.295 inches and 1.315 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2953 inches and 0.2963 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 0.870 inches and 0.880 inches

Thread Size:

0.250 inches

Special Features:

0.0468 oversize shank, restricted usage, repair work only.

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740 or steel comp e4340

Material Specification:

Mil-s-6758 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response or mil-s-5000 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

81205-bacb30ma manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.