# NSN 5320-01-410-8390

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-410-8390

## Fastener Length:

Between 0.365 inches and 0.385 inches

## Head Style:

Undersized oval countersunk

## Head Height:

Between 0.004 inches and 0.006 inches

## Shank Diameter:

Between 0.186 inches and 0.189 inches

#### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

## Head Minor Diameter:

Between 0.198 inches and 0.208 inches

## **Countersink Height:**

0.046 inches

## **Countersink Angle:**

Between 70.0 degrees and 130.0 degrees

## Heat Treatment:

H-32 strain hardened

## Material:

Aluminum alloy 5056

## **Material Specification:**

Qq-a-430 federal specification single material response

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625, type ii, class 1 military specification single treatment response

## **Specification Data:**

80205-nas1097 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# Fiig:

A040a0

## Mil-std (military Standard):

Mil-a-8625 spec.