NSN 5320-01-411-6425

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-411-6425

Fastener Length:

0.662 inches

Head Style:

Hexagon

Head Height:

0.096 inches

Shank Diameter:

Between 0.1625 inches and 0.1645 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded stem

Lubrication:

Carbo wax or cetyl alcohol or paraffin wax

Grip Length:

Between 0.282 inches and 0.344 inches

Width Across Flats:

Between 0.244 inches and 0.250 inches

Min. Tensile Strength (psi):

900 pounds per square inch

Shear Strength:

3150 double pounds per square inch

Special Features:

Powder blast top of nut head.

Material:

Titanium alloy uns r56400 nut

Material Specification:

Ams5639 assn standard single material response sleeve or ams5641 assn standard single material response sleeve or ams5731 assn standard 1st material response sleeve or ams5732 assn standard 2nd material response sleeve or ams5737 assn standard 3rd material response sleeve

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Specification Data:

1w025-03a054 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0