NSN 5320-01-411-6427

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-411-6427

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| |
| Right-hand Identification Code Color: |
| |
| Green |
| Fastener Length: Between 1.187 inches and 1.207 inches |
| |
| Head Style: Err-090 |
| |
| Head Height: Between 0.150 inches and 0.160 inches |
| |
| Width Between Flats: |
| Between 0.1895 inches and 0.1930 inches Shank Diameter: |
| |
| Between 0.4365 inches and 0.4370 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.641 inches and 0.676 inches |
| Lubrication: |
| Cetyl alcohol |
| Grip Length: |
| Between 0.557 inches and 0.567 inches |
| Min. Tensile Strength (psi): |
| 25800 pounds per square inch |
| Thread Size: |
| 0.438 inches |
| Shear Strength: |
| 37500 double pounds per square inch |
| Special Features: |
| Powder blast top of head, with color dark green on thread end. |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams5662 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 1w025-03a064 manufacturers standard |
| Shelf Life: |

N/a

NSN 5320-01-411-6427

Pin-rivet - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A528u0