

View Online at <https://aerobasegroup.com/nsn/5320-01-411-7951>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.440 inches and 0.460 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.1885 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**Lubrication:**

Solid film

**Grip Length:**

Between 0.120 inches and 0.130 inches

**Min. Tensile Strength (psi):**

3180 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

5380 double pounds per square inch

**Special Features:**

Solid film lube per mil-I-46010, type i

**Material:**

Iron alloy 660

**Material Specification:**

Ams5737 assn standard single material response or ams5731 assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-hl48 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0