## NSN 5320-01-411-7960

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-411-7960 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.065 inches and 1.085 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.745 inches and 0.755 inches Min. Tensile Strength (psi): 2000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 6130 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** 1/64" oversize shank. For repair work only. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 73197-hl111 manufacturers standard Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5320-01-411-7960

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0