NSN 5320-01-411-8354

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-411-8354 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** Between 1.937 inches and 1.957 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.436 inches and 0.437 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.881 inches and 0.889 inches **Tip Diameter:** Between 0.426 inches and 0.431 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** W/s: aircraft, b-1b **Grip Length:** Between 1.307 inches and 1.317 inches Min. Tensile Strength (psi): 25800 pounds per square inch **Thread Size:** 0.438 inches **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: **Unit Of Measure:**

N/a
Unit Of Measure:
-Demilitarization:

NSN 5320-01-411-8354

Pin-rivet - Page 2 of 2



Fiig:

A528u0