

View Online at <https://aerobasegroup.com/nsn/5320-01-411-9035>

Identification Code Color:

Gray

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2575 inches and 0.2595 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.463 inches and 0.507 inches

Expansion Device:

Threaded stem and expander

Lubrication:

Cetyl alcohol or carbo wax or paraffin wax

Grip Length:

Between 0.100 inches and 0.150 inches

Features Provided:

Drive nut

Min. Tensile Strength (psi):

2100 pounds per square inch

Shear Strength:

7900 double pounds per square inch

Countersink Angle:

Between 129.0 degrees and 131.0 degrees

Special Features:

Powder blast top of head.

Heat Treatment:

Annealed sleeve

Material:

Titanium alloy uns r56400 nut

Material Specification:

Mil-t-9047 military specification single material response nut or ams4928 assn standard single material response nut or ams4967 assn standard single material response nut

Surface Treatment:

Phosphate nut

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Specification Data:

98524-mbf2113 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-t-9047 spec.