

View Online at <https://aerobasegroup.com/nsn/5320-01-411-9035>

**Identification Code Color:**

Gray

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2575 inches and 0.2595 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.463 inches and 0.507 inches

**Expansion Device:**

Threaded stem and expander

**Lubrication:**

Cetyl alcohol or carbo wax or paraffin wax

**Grip Length:**

Between 0.100 inches and 0.150 inches

**Features Provided:**

Drive nut

**Min. Tensile Strength (psi):**

2100 pounds per square inch

**Shear Strength:**

7900 double pounds per square inch

**Countersink Angle:**

Between 129.0 degrees and 131.0 degrees

**Special Features:**

Powder blast top of head.

**Heat Treatment:**

Annealed sleeve

**Material:**

Titanium alloy uns r56400 nut

**Material Specification:**

Mil-t-9047 military specification single material response nut or ams4928 assn standard single material response nut or ams4967 assn standard single material response nut

**Surface Treatment:**

Phosphate nut

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response sleeve

**Specification Data:**

98524-mbf2113 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-t-9047 spec.