## NSN 5320-01-412-1280

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-412-1280

| Fastener Length:   |
|--|
| 1.360 inches   |
| Head Style:  |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter:  |
| Between 0.388 inches and 0.390 inches  |
| Shank Style:   |
| Self-plugging mechanically locked stem   |
| Head Major Diameter:   |
| 0.763 inches   |
| Expansion Device:  |
| Serrated stem-type w   |
| Grip Length:   |
| Between 1.031 inches and 1.095 inches  |
| Min. Tensile Strength (psi):   |
| 5970 pounds per square inch  |
| Shear Strength:  |
| 10380 single pounds per square inch  |
| Countersink Angle:   |
| Between 98.0 degrees and 101.0 degrees   |
| Special Features:  |
| 0.016 oversize shank. For repair work only.  |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5737 assn standard single material response                                     |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response                            |
| Specification Data:  |
| 81755-c9512 manufacturers specification control                                    |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |