

View Online at <https://aerobasegroup.com/nsn/5320-01-412-4884>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.708 inches and 1.728 inches

Head Style:

Err-090

Head Height:

Between 0.068 inches and 0.078 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3579 inches and 0.3589 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.505 inches and 0.535 inches

Lubrication:

Cetyl alcohol or cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.183 inches and 1.193 inches

Min. Tensile Strength (psi):

6300 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

19200 double pounds per square inch

Special Features:

3/64" oversize shank, for repair work only.

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

73197-hl202 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.