

View Online at <https://aerobasegroup.com/nsn/5320-01-412-4884>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.708 inches and 1.728 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.068 inches and 0.078 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3579 inches and 0.3589 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.505 inches and 0.535 inches

**Lubrication:**

Cetyl alcohol or cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 1.183 inches and 1.193 inches

**Min. Tensile Strength (psi):**

6300 pounds per square inch

**Thread Size:**

0.312 inches

**Shear Strength:**

19200 double pounds per square inch

**Special Features:**

3/64" oversize shank, for repair work only.

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

73197-hl202 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.