NSN 5320-01-412-6844

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-412-6844

Fastener Length:
Between 0.745 inches and 0.755 inches
Head Style:
Countersunk w/ reverse chamfer
Head Height:
Between 0.041 inches and 0.051 inches
Hole Diameter:
Between 0.133 inches and 0.139 inches
Shank Diameter:
Between 0.182 inches and 0.188 inches
Shank Style:
Tubular
Head Major Diameter:
Between 0.351 inches and 0.367 inches
Hole Depth:
0.155 inches
Shear Strength:
32000 double pounds per square inch
Countersink Angle:
Between 148.0 degrees and 150.0 degrees
Material:
Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012
or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp
1020 or steel comp 1021 or steel comp 1022
Material Specification:
66 federal standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No No
Filg:
A040a0