## NSN 5320-01-413-2068

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

Yellow

**Thread Direction:** 

**Identification Code Color:** 

За



View Online at https://aerobasegroup.com/nsn/5320-01-413-2068

Fastener Length:
Between 1.723 inches and 1.743 inches
Head Style:
Err-090
Head Height:
Between 0.102 inches and 0.112 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3271 inches and 0.3276 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.475 inches and 0.505 inches
Lubrication:
Solid film and cetyl alcohol
Grip Length:
Between 1.183 inches and 1.193 inches
Min. Tensile Strength (psi):
12300 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
19160 double pounds per square inch
Special Features:
0.0156 oversize part, restricted usage, for repair work only.
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
1w025-03a064 manufacturers standard
Shelf Life:
N/a

## NSN 5320-01-413-2068

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0