## NSN 5320-01-413-2069

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

Yellow

**Thread Direction:** 

Fastener Length:

**Identification Code Color:** 

За



View Online at https://aerobasegroup.com/nsn/5320-01-413-2069

Head Style:  Err-090  Head Height:  Between 0.102 inches and 0.112 inches  Width Between Flats:  Between 0.1270 inches and 0.1295 inches  Shank Diameter:  Between 0.3271 inches and 0.3276 inches  Shank Style:  Pin-rivet, straight, threaded  Head Major Diameter:  Between 0.475 inches and 0.505 inches  Lubrication:  Solid film and cetyl alcohol  Grip Length:  Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi):  12300 pounds per square inch  Thread Size:  0.312 inches  Shear Strength:  19160 double pounds per square inch  Special Features:  0.0156 oversize part, restricted usage, for repair work only.  Material:  Nickel alloy 718  Material Specification:  Ams5662 assn standard single material response
Head Height: Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches Shank Diameter: Between 0.3271 inches and 0.3276 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.475 inches and 0.505 inches Lubrication: Solid film and cetyl alcohol Grip Length: Between 0.495 inches and 0.505 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Special Features: 0.0156 oversize part, restricted usage, for repair work only. Material: Nickel alloy 718 Material Specification:
Between 0.102 inches and 0.112 inches  Width Between Flats: Between 0.1270 inches and 0.1295 inches  Shank Diameter: Between 0.3271 inches and 0.3276 inches  Shank Style: Pin-rivet, straight, threaded  Head Major Diameter: Between 0.475 inches and 0.505 inches  Lubrication: Solid film and cetyl alcohol  Grip Length: Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi): 12300 pounds per square inch  Thread Size: 0.312 inches  Shear Strength: 19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
Width Between Flats: Between 0.1270 inches and 0.1295 inches Shank Diameter: Between 0.3271 inches and 0.3276 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.475 inches and 0.505 inches Lubrication: Solid film and cetyl alcohol Grip Length: Between 0.495 inches and 0.505 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Special Features: 0.0156 oversize part, restricted usage, for repair work only. Material: Nickel alloy 718 Material Specification:
Between 0.1270 inches and 0.1295 inches  Shank Diameter: Between 0.3271 inches and 0.3276 inches  Shank Style: Pin-rivet, straight, threaded  Head Major Diameter: Between 0.475 inches and 0.505 inches  Lubrication: Solid film and cetyl alcohol  Grip Length: Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi): 12300 pounds per square inch  Thread Size: 0.312 inches  Shear Strength: 19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
Shank Diameter: Between 0.3271 inches and 0.3276 inches  Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.475 inches and 0.505 inches Lubrication: Solid film and cetyl alcohol Grip Length: Between 0.495 inches and 0.505 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Special Features: 0.0156 oversize part, restricted usage, for repair work only. Material: Nickel alloy 718 Material Specification:
Between 0.3271 inches and 0.3276 inches  Shank Style: Pin-rivet, straight, threaded  Head Major Diameter: Between 0.475 inches and 0.505 inches  Lubrication: Solid film and cetyl alcohol  Grip Length: Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi): 12300 pounds per square inch  Thread Size: 0.312 inches  Shear Strength: 19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.475 inches and 0.505 inches Lubrication: Solid film and cetyl alcohol Grip Length: Between 0.495 inches and 0.505 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Special Features: 0.0156 oversize part, restricted usage, for repair work only. Material: Nickel alloy 718 Material Specification:
Pin-rivet, straight, threaded  Head Major Diameter:  Between 0.475 inches and 0.505 inches  Lubrication:  Solid film and cetyl alcohol  Grip Length:  Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi):  12300 pounds per square inch  Thread Size:  0.312 inches  Shear Strength:  19160 double pounds per square inch  Special Features:  0.0156 oversize part, restricted usage, for repair work only.  Material:  Nickel alloy 718  Material Specification:
Head Major Diameter:  Between 0.475 inches and 0.505 inches  Lubrication:  Solid film and cetyl alcohol  Grip Length:  Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi): 12300 pounds per square inch  Thread Size: 0.312 inches  Shear Strength: 19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material:  Nickel alloy 718  Material Specification:
Between 0.475 inches and 0.505 inches  Lubrication:  Solid film and cetyl alcohol  Grip Length:  Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi):  12300 pounds per square inch  Thread Size:  0.312 inches  Shear Strength:  19160 double pounds per square inch  Special Features:  0.0156 oversize part, restricted usage, for repair work only.  Material:  Nickel alloy 718  Material Specification:
Lubrication: Solid film and cetyl alcohol Grip Length: Between 0.495 inches and 0.505 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Special Features: 0.0156 oversize part, restricted usage, for repair work only. Material: Nickel alloy 718 Material Specification:
Solid film and cetyl alcohol  Grip Length: Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi): 12300 pounds per square inch  Thread Size: 0.312 inches  Shear Strength: 19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
Grip Length:  Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi):  12300 pounds per square inch  Thread Size:  0.312 inches  Shear Strength:  19160 double pounds per square inch  Special Features:  0.0156 oversize part, restricted usage, for repair work only.  Material:  Nickel alloy 718  Material Specification:
Between 0.495 inches and 0.505 inches  Min. Tensile Strength (psi): 12300 pounds per square inch  Thread Size: 0.312 inches  Shear Strength: 19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
Min. Tensile Strength (psi):  12300 pounds per square inch  Thread Size:  0.312 inches  Shear Strength:  19160 double pounds per square inch  Special Features:  0.0156 oversize part, restricted usage, for repair work only.  Material:  Nickel alloy 718  Material Specification:
12300 pounds per square inch  Thread Size: 0.312 inches  Shear Strength: 19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
Thread Size:  0.312 inches  Shear Strength:  19160 double pounds per square inch  Special Features:  0.0156 oversize part, restricted usage, for repair work only.  Material:  Nickel alloy 718  Material Specification:
0.312 inches  Shear Strength: 19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
Shear Strength: 19160 double pounds per square inch Special Features: 0.0156 oversize part, restricted usage, for repair work only. Material: Nickel alloy 718 Material Specification:
19160 double pounds per square inch  Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
Special Features: 0.0156 oversize part, restricted usage, for repair work only.  Material: Nickel alloy 718  Material Specification:
0.0156 oversize part, restricted usage, for repair work only.  Material:  Nickel alloy 718  Material Specification:
Material: Nickel alloy 718 Material Specification:
Nickel alloy 718  Material Specification:
Material Specification:
•
Ams5662 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
1w025-03a064 manufacturers standard
Shelf Life:
Shelf Life: N/a

## NSN 5320-01-413-2069

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0