NSN 5320-01-413-2071

Pin-rivet - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5320-01-413-2071

Tillead Direction.						
Right-hand						
Identification Code Color:						
Yellow						
Fastener Length:						
Between 0.925 inches and 0.945 inches						
Head Style:						
Err-090						
Head Height:						
Between 0.080 inches and 0.090 inches						
Width Between Flats:						
Between 0.0947 inches and 0.0967 inches						
Shank Diameter:						
Between 0.2646 inches and 0.2651 inches						
Shank Style:						
Pin-rivet, straight, threaded						
Head Major Diameter:						
Between 0.415 inches and 0.440 inches						
Lubrication:						
Solid film and cetyl alcohol						
Grip Length:						
Between 0.495 inches and 0.505 inches						
Min. Tensile Strength (psi):						
7750 pounds per square inch						
Thread Size:						
0.250 inches						
Shear Strength:						
12260 double pounds per square inch						
Special Features:						
0.0156 oversize part, restricted usage, for repair work only.						
Material:						
Nickel alloy 718						
Material Specification:						
Ams5662 assn standard single material response						
Thread Series Designator:						
Unjf						
Specification Data:						
1w025-03a064 manufacturers standard						
Shelf Life:						
N/a						

NSN 5320-01-413-2071

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A528u0