NSN 5320-01-413-2074


Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

3a



Identification Code Color: Yellow **Fastener Length:** Between 0.737 inches and 0.757 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches Shank Diameter: Between 0.2646 inches and 0.2651 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.415 inches and 0.440 inches Lubrication: Solid film and cetyl alcohol Grip Length: Between 0.307 inches and 0.317 inches Min. Tensile Strength (psi): 7750 pounds per square inch **Thread Size:** 0.250 inches Shear Strength: 12260 double pounds per square inch **Special Features:** 0.0156 oversize part, restricted usage, for repair work only. Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 1w025-03a064 manufacturers standard Shelf Life: N/a



NSN 5320-01-413-2074

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

