## NSN 5320-01-413-2704

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-2704

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Yellow
Fastener Length:
Between 0.973 inches and 0.993 inches
Head Style:
Err-090
Head Height:
Between 0.102 inches and 0.112 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3271 inches and 0.3276 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.475 inches and 0.505 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.433 inches and 0.443 inches
Min. Tensile Strength (psi):
12300 pounds per square inch
Thread Size:
0.312 inches
Shear Strength:
19160 double pounds per square inch
Special Features:
Powder blast top of head. 0.0156 oversize part, restricted usage, for repair work only.
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
1w025-03a064 manufacturers standard
Shelf Life:
N/a

## NSN 5320-01-413-2704

Pin-rivet - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A528u0