NSN 5320-01-413-2709

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-2709

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Yellow
Fastener Length:
Between 0.975 inches and 0.995 inches
Head Style:
Err-090
Head Height:
Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.2021 inches and 0.2026 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.620 inches and 0.630 inches
Min. Tensile Strength (psi):
4350 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
7060 double pounds per square inch
Special Features:
Powder blast top of head. 0.0156 oversize part, restricted usage, for repair work only.
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
1w025-03a064 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-413-2709

Pin-rivet - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A528u0