## NSN 5320-01-413-3293

Pin-rivet - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

3a

View Online at https://aerobasegroup.com/nsn/5320-01-413-3293

**Right-hand** Identification Code Color: Yellow **Fastener Length:** Between 1.100 inches and 1.120 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches Shank Diameter: Between 0.2021 inches and 0.2026 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.357 inches and 0.377 inches Lubrication: Solid film and cetyl alcohol Grip Length: Between 0.745 inches and 0.755 inches Min. Tensile Strength (psi): 4350 pounds per square inch **Thread Size:** 0.190 inches Shear Strength: 7060 double pounds per square inch **Special Features:** 0.0156 oversize part, restricted usage, for repair work only. Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 1w025-03a064 manufacturers standard Shelf Life: N/a



## NSN 5320-01-413-3293

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

