## NSN 5320-01-413-5126

Blind Rivet - Page 1 of 1

A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-413-5126

Head Style:
Hexagon
Head Height:
0.160 inches
Shank Diameter:
Between 0.3095 inches and 0.3115 inches
Expansion Device: Threaded stem
Lubrication:
Dry film or cetyl alcohol or carbo wax or paraffin wax
Grip Length:
Between 0.657 inches and 0.719 inches
Width Across Flats:
Between 0.429 inches and 0.437 inches
Features Provided:
Drive nut and self-locking  Min. Tanaila Strangth (nai):
Min. Tensile Strength (psi):
3600 pounds per square inch
Shear Strength:
11350 double pounds per square inch
Special Features:
Dry film lubricant is prohibited on exposed surface of nut head.
Material:
Titanium alloy uns r56400 nut
Material Specification:
Ams5639 assn standard single material response sleeve or ams5641 assn standard single material response sleeve or ams5731 assn
standard single material response sleeve or ams5732 assn standard single material response sleeve or ams5737 assn standard single
material response sleeve  Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response sleeve
Specification Data:
1w025-03a054 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No Eller
Fiig: