## NSN 5320-01-413-5128

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-5128

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Identification Code Color:   |
| Blue   |
| Fastener Length:   |
| Between 1.9875 inches and 2.0075 inches  |
| Head Style:  |
| Err-090  |
| Head Height:   |
| Between 0.178 inches and 0.188 inches  |
| Width Between Flats:   |
| Between 0.2207 inches and 0.2242 inches  |
| Shank Diameter:  |
| Between 0.4990 inches and 0.4995 inches  |
| Shank Style:   |
| Pin-rivet, straight, threaded  |
| Head Major Diameter:   |
| Between 0.735 inches and 0.770 inches  |
| Lubrication:   |
| Cetyl alcohol  |
| Grip Length:   |
| Between 1.3075 inches and 1.3175 inches  |
| Min. Tensile Strength (psi):   |
| 25500 pounds per square inch   |
| Thread Size:   |
| 0.500 inches   |
| Shear Strength:  |
| 37300 double pounds per square inch  |
| Special Features:  |
| Powder blast top of head, with color light blue on thread end.                                   |
| Material:  |
| Titanium alloy uns r56400  |
| Material Specification:  |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 76823-03a076 manufacturers standard  |
| Shelf Life:  |
| N/a  |

## NSN 5320-01-413-5128

Pin-rivet - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A528u0