NSN 5320-01-413-5128

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-5128

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 1.9875 inches and 2.0075 inches
Head Style:
Err-090
Head Height:
Between 0.178 inches and 0.188 inches
Width Between Flats:
Between 0.2207 inches and 0.2242 inches
Shank Diameter:
Between 0.4990 inches and 0.4995 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.735 inches and 0.770 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 1.3075 inches and 1.3175 inches
Min. Tensile Strength (psi):
25500 pounds per square inch
Thread Size:
0.500 inches
Shear Strength:
37300 double pounds per square inch
Special Features:
Powder blast top of head, with color light blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
76823-03a076 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-413-5128

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0