

View Online at <https://aerobasegroup.com/nsn/5320-01-413-5449>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.1970 inches and 0.1990 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.2700 inches and 0.3016 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or cetyl alcohol or carbo wax or paraffin wax

Grip Length:

Between 1.032 inches and 1.094 inches

Features Provided:

Drive nut and self-locking

Min. Tensile Strength (psi):

1250 pounds per square inch

Shear Strength:

4600 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Dry film lube is prohibited on exposed surfaces of nut head.

Material:

Stainless steel sleeve

Material Specification:

Ams4928 assn standard single material response nut or ams4967 assn standard single material response nut

Surface Treatment:

Passivate sleeve

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response sleeve

Specification Data:

1w025-03a053 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0