

View Online at <https://aerobasegroup.com/nsn/5320-01-413-6122>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Brown

**Fastener Length:**

Between 0.912 inches and 0.932 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.2021 inches and 0.2026 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.296 inches and 0.301 inches

**Tip Diameter:**

Between 0.1810 inches and 0.1840 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.557 inches and 0.567 inches

**Min. Tensile Strength (psi):**

2600 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

8100 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0