NSN 5320-01-413-6124

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-6124 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Brown **Fastener Length:** Between 1.050 inches and 1.070 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.264 inches and 0.265 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.389 inches and 0.394 inches Tip Diameter: Between 0.241 inches and 0.244 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.620 inches and 0.630 inches Min. Tensile Strength (psi): 4400 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 13800 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-413-6124

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0