NSN 5320-01-413-6127

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-6127

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Black
Fastener Length:
Between 2.660 inches and 2.680 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.1582 inches and 0.1617 inches
Shank Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.7556 inches and 0.7604 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
W/s: aircraft, b-2 bomber (atb)
Grip Length:
Between 2.120 inches and 2.130 inches
Min. Tensile Strength (psi):
14000 pounds per square inch
Thread Size:
0.375 inches
Countersink Angle:
100.0 degrees
Special Features:
Grit blast top of head, with color light blue on thread end.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
73197-hlt453 manufacturers standard
Shelf Life:

N/a

NSN 5320-01-413-6127

Pin-rivet - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A528u0