NSN 5320-01-413-6129

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Green

Thread Direction:

Fastener Length:

Identification Code Color:

За



View Online at https://aerobasegroup.com/nsn/5320-01-413-6129

rusterier Eerigui.	
Between 1.240 inches and 1.260 inches	
Head Style:	
Flush countersunk	
Width Between Flats:	
Between 0.1270 inches and 0.1295 inches	
Shank Diameter:	
Between 0.3110 inches and 0.3120 inches	
Shank Style:	
Pin-rivet, straight, threaded	
Head Major Diameter:	
Between 0.6287 inches and 0.6335 inches	
Lubrication:	
Solid film and cetyl alcohol	
Grip Length:	
Between 0.745 inches and 0.755 inches	
Min. Tensile Strength (psi):	
12300 pounds per square inch	
Thread Size:	
0.312 inches	
Shear Strength:	
19160 double pounds per square inch	
Countersink Angle:	
100.0 degrees	
Special Features:	
Powder blast top of head, with color green on thread end.	
Material:	
Nickel alloy 718	
Material Specification:	
Ams5662 assn standard single material response	
Thread Series Designator:	
Unjf	
Specification Data:	
76823-03a063 manufacturers standard	
Shelf Life:	
N/a	

NSN 5320-01-413-6129

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0