NSN 5320-01-413-9001

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-9001 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Brown **Fastener Length:** Between 0.662 inches and 0.682 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.2021 inches and 0.2026 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.296 inches and 0.301 inches Tip Diameter: Between 0.181 inches and 0.184 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.307 inches and 0.317 inches Min. Tensile Strength (psi): 2600 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 8100 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-413-9001

Pin-rivet - Page 2 of 2



Fiig:

A528u0