NSN 5320-01-413-9416

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-413-9416



Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Yellow

Fastener Length:

Between 1.800 inches and 1.820 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2641 inches and 0.2651 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

Lubrication:

Solid film and cetyl alcohol

Grip Length:

Between 1.370 inches and 1.380 inches

Min. Tensile Strength (psi):

7750 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

12260 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Caution, restricted usage, oversize parts, for repair work only.

Material:

Nickel alloy 718

Material Specification:

Ams5662 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

1w025-03a063 manufacturers standard

Shelf Life:

N/a

NSN 5320-01-413-9416

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

