NSN 5320-01-413-9420

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-9420

Thread Oleran					
Thread Class:					
3a					
Thread Direction:					
Right-hand					
Identification Code Color:					
Yellow					
Fastener Length:					
Between 1.237 inches and 1.257 inches					
Head Style:					
Flush countersunk					
Width Between Flats:					
Between 0.0947 inches and 0.0967 inches					
Shank Diameter:					
Between 0.2641 inches and 0.2651 inches					
Shank Style:					
Pin-rivet, straight, threaded					
Head Major Diameter:					
Between 0.5018 inches and 0.5066 inches					
Lubrication:					
Solid film and cetyl alcohol					
Grip Length:					
Between 0.807 inches and 0.817 inches					
Min. Tensile Strength (psi):					
7750 pounds per square inch					
Thread Size:					
0.250 inches					
Shear Strength:					
12260 double pounds per square inch					
Countersink Angle:					
100.0 degrees					
Special Features:					
Caution, restricted usage, for repair work only.					
Material:					
Nickel alloy 718					
Material Specification:					
Ams5662 assn standard single material response					
Thread Series Designator:					
Unjf					
Specification Data:					
1w025-03a063 manufacturers standard					
Shelf Life:					

N/a

NSN 5320-01-413-9420

Pin-rivet - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0