NSN 5320-01-413-9424 Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-413-9424
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Yellow
Fastener Length:
Between 0.737 inches and 0.757 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2646 inches and 0.2651 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5018 inches and 0.5066 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.307 inches and 0.317 inches
Min. Tensile Strength (psi):
7750 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
12260 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Powder blast top of head. Caution, restricted usage, for repair work only.
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-413-9424

Pin-rivet - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

1w025-03a063 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0