

View Online at <https://aerobasegroup.com/nsn/5320-01-413-9425>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Yellow

**Fastener Length:**

Between 0.800 inches and 0.820 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2641 inches and 0.2651 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.5018 inches and 0.5066 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.370 inches and 0.380 inches

**Min. Tensile Strength (psi):**

7750 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

12260 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Powder blast top of head. Caution, restricted usage, for repair work only.

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

1w025-03a063 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0