
# NSN 5320-01-413-9426

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Identification Code Color:

Yellow

#### Fastener Length:

Between 0.863 inches and 0.883 inches

#### **Head Style:**

Flush countersunk

### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

### Shank Diameter:

Between 0.2646 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.5018 inches and 0.5066 inches

## Lubrication:

Cetyl alcohol

Grip Length:

Between 0.433 inches and 0.443 inches

## Min. Tensile Strength (psi):

7750 pounds per square inch

## Thread Size:

0.250 inches

### Shear Strength:

12260 double pounds per square inch

### **Countersink Angle:**

100.0 degrees

### **Special Features:**

Powder blast top of head. Caution, restricted usage, oversize parts, for repair work only.

## Material:

Nickel alloy 718

# Material Specification:

Ams5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-413-9426

Pin-rivet - Page 2 of 2

Specification Data:

1w025-03a063 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

