NSN 5320-01-414-1449

Pin-rivet - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5320-01-414-1449

Right-hand				
Identification Code Color:				
Yellow				
Fastener Length:				
Between 1.425 inches and 1.445 inches				
Head Style:				
Flush countersunk				
Width Between Flats:				
Between 0.0947 inches and 0.0967 inches				
Shank Diameter:				
Between 0.2646 inches and 0.2651 inches				
Shank Style:				
Head Major Diameter:				
Between 0.5018 inches and 0.5066 inches				
Lubrication:				
Cetyl alcohol				
Grip Length:				
Between 0.995 inches and 1.005 inches				
Min. Tensile Strength (psi):				
7750 pounds per square inch				
Thread Size:				
0.250 inches				
Shear Strength:				
12260 double pounds per square inch				
Countersink Angle:				
100.0 degrees				
Special Features:				
Powder blast top of head. Caution restricted usage. Oversize part, for repair work only.				
Material:				
Nickel alloy 718				
Material Specification:				
Ams5662 assn standard single material response				
Surface Treatment:				
Passivate				
Surface Treatment Specification:				
Qq-p-35 federal specification single treatment response				
Thread Series Designator:				
Unjf				

NSN 5320-01-414-1449

Pin-rivet - Page 2 of 2



Spec	cific	ation	Data:
------	-------	-------	-------

1w025-03a063 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0