

View Online at <https://aerobasegroup.com/nsn/5320-01-414-2165>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Identification Code Color:**

Bronze

**Fastener Length:**

Between 1.324 inches and 1.344 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.404 inches and 0.406 inches

**Shank Style:**

Pin-rivet, tapered, threaded

**Head Major Diameter:**

Between 0.580 inches and 0.591 inches

**Tip Diameter:**

Between 0.364 inches and 0.368 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.683 inches and 0.693 inches

**Min. Tensile Strength (psi):**

7200 pounds per square inch

**Thread Size:**

0.375 inches

**Shear Strength:**

24000 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Part number indicates collar attachment

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5626 spec.