

View Online at <https://aerobasegroup.com/nsn/5320-01-414-2165>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Bronze

Fastener Length:

Between 1.324 inches and 1.344 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.404 inches and 0.406 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.580 inches and 0.591 inches

Tip Diameter:

Between 0.364 inches and 0.368 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.683 inches and 0.693 inches

Min. Tensile Strength (psi):

7200 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

24000 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Part number indicates collar attachment

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.