

View Online at <https://aerobasegroup.com/nsn/5320-01-414-2916>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.052 inches and 2.072 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.326 inches and 0.327 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.628 inches and 0.633 inches

Tip Diameter:

Between 0.302 inches and 0.306 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.557 inches and 1.567 inches

Min. Tensile Strength (psi):

9200 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

16000 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Part number indicates collar/rivet combination

Material:

Steel comp 4140

Material Specification:

Mil-s-5626 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.