
# NSN 5320-01-414-3656

Pin-rivet - Page 1 of 2



AeroBase Group

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Identification Code Color:

Yellow

#### Fastener Length:

Between 1.8475 inches and 1.8675 inches

#### **Head Style:**

Flush countersunk

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3266 inches and 0.3276 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

### Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.3075 inches and 1.3175 inches

### Min. Tensile Strength (psi):

12300 pounds per square inch

### Thread Size:

0.312 inches

#### Shear Strength:

19160 double pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Powder blast top of head, with color yellow on thread end

## Material:

Nickel alloy 718

# Material Specification:

Ams 5662 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-414-3656

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

