

View Online at <https://aerobasegroup.com/nsn/5320-01-414-3659>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.795 inches and 1.815 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0067 inches and 0.0947 inches

Shank Diameter:

Between 0.2707 inches and 0.2807 inches

Shank Style:

Head Major Diameter:

Between 0.5066 inches and 0.6018 inches

Grip Length:

Between 1.495 inches and 1.505 inches

Min. Tensile Strength (psi):

5820 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

11800 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Pin and collar combination

Material:

Steel comp e4340 or steel comp 4130 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.