

View Online at <https://aerobasegroup.com/nsn/5320-01-414-3660>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.607 inches and 1.627 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0067 inches and 0.0947 inches

**Shank Diameter:**

Between 0.2707 inches and 0.2807 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.5060 inches and 0.6018 inches

**End Application:**

W/s: aircraft, stratolifter c-135

**Grip Length:**

Between 1.307 inches and 1.317 inches

**Min. Tensile Strength (psi):**

5820 pounds per square inch

**Thread Size:**

0.250 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Pin and collar combination

**Material:**

Steel comp e4340 or steel comp 4130 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5000 spec.