

View Online at <https://aerobasegroup.com/nsn/5320-01-414-3662>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.263 inches and 1.283 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0701 inches and 0.0806 inches

Shank Diameter:

Between 0.2172 inches and 0.2182 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3253 inches and 0.3303 inches

Grip Length:

Between 0.932 inches and 0.942 inches

Min. Tensile Strength (psi):

2000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

7100 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Pin and collar combination

Material:

Steel comp e4340 or steel comp 4130 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.